

## PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



### TECHNICAL SPECIFICATIONS

#### DIMENSIONS

|        |                    |
|--------|--------------------|
| Length | 430mm • 16.9"      |
| Width  | 260mm • 10.2"      |
| Height | 310mm • 12.2"      |
| Weight | 10.3 kgs • 22.6lbs |

#### FEEDING

|                 |                         |
|-----------------|-------------------------|
| Pressure range  | 5.5 -7 bar / 78 -99 psi |
| Air consumption | 12 L/s - 25 cuft/min    |

#### PERFORMANCE

|                    |                           |
|--------------------|---------------------------|
| Max. tension force | 9000N -6.5bar-92psi       |
| Tensioning speed   | 6mt/m                     |
| Sealing            | Seal double notches       |
| Joint strength     | 80% of breaking strength* |
| Gear ratio         | -                         |

\* variable according to strap type

### MODEL

| CODE    | TYPE                      | STRAP                   | THICKNESS       |
|---------|---------------------------|-------------------------|-----------------|
| T411943 | ITA41 - 3/4" - 9000N-3B   | R 850N/mm <sup>2</sup>  | 0.024" - 0.039" |
|         |                           | R 1100N/mm <sup>2</sup> | 0.025" - 0.031" |
| T412543 | ITA41 - 1" - 9000N-3B     | R 850N/mm <sup>2</sup>  | 0.024" - 0.039" |
|         |                           | R 1100N/mm <sup>2</sup> | 0.025" - 0.031" |
| T413243 | ITA41 - 1 1/4" - 9000N-3B | R 850N/mm <sup>2</sup>  | 0.024" - 0.039" |
|         |                           | R 1100N/mm <sup>2</sup> | 0.025" - 0.031" |

### SEAL DOUBLE NOTCHES

